

## AMENDMENTS TO THE CLAIMS

1-20. (Canceled)

21. (Currently Amended) A system for managing the display of media on a plurality of media systems of a facility, the system comprising:
- a data stream source operable to store audio-visual files in digital format including multiple instances of each of the audio-visual files for simultaneous access by a plurality of media players;
  - a first decoder in communication with the data stream source and operable to receive a first audio-visual file selected from the audio-visual files, the first decoder further operable to convert the first audio-visual file into a first analog signal;
  - a second decoder in communication with the data stream source and operable to receive a second audio-visual file selected from the audio-visual files, the ~~second~~first decoder further operable to convert the second audio-visual file into a second analog signal, each of the first decoder and the second decoder communicating with the data stream source through a separate communications channel;
  - a controller in communication with the data stream source~~first and second decoders~~ through a data network and operable to select the first audio-visual file in response to a selection made by a user through a user interface provided by the controller, the user interface communicates prompts and selections to the user through one of the plurality of media players, the user interface including a phone interface and a computer interface to the controller for receiving user input, the selection of the first audio-visual file being made in response to the controller communicating with the first decoder using an infrared signal, the controller being further operable to select a second audio-visual file, the selection of the second audio-visual file being made in response to the controller communicating with the second decoder using an infrared signal, wherein streams of the audio-files from the data stream source are not communicated through the data network;
  - a first modulator in communication with the first decoder and operable to receive the first analog signal and modulate the first analog signal for communication over a first coaxial cable; ~~[[and]]~~
  - a second modulator in communication with the second decoder and operable to receive the second analog signal and modulate the second analog signal for communication over a

second coaxial cable, the first coaxial cable and the second coaxial cable are part of a coaxial cable network separate from the data network; and

a combiner in communication with the first modulator and the second modulator, the combiner operable to combine the first analog signal and second analog signal into a combined analog signal, each of the first decoder and second decoder being associated with a dedicated channel in the combined analog signal, a plurality of dedicated channels available to each of the plurality of media players through the coaxial cable network, one or more of the plurality of media players decoding the first analog signal and the second analog signal from the combined analog signal.

22. (Currently Amended) The system of Claim 21, wherein the second coaxial cable communicates with a second media player, and wherein [[is]] the first coaxial cable communicates with a first media player.
23. (Currently Amended) The system of Claim 21, ~~and further comprising a combiner in communication with the first and second modulators and operable to combine the first and second analog signals into a combined analog signal wherein each of a plurality of decoders including the first decoder and second decoder being associated with a dedicated channel in the combined analog signal.~~
24. (Currently Amended) The system of Claim 21, ~~wherein and further comprising a combiner in communication with the first and second modulators and operable to combine the first and second analog signals~~ are combined into the[[a]] combined analog signal having two channels, a first of the two channels carrying the first analog signal and the second of the two channels carrying the second analog signal, the combined analog signal being communicated over the[[a]] coaxial cable network to a first media player, the first media player operable to select the first channel for display of the content of the first audio-visual file.
25. (Currently Amended) The system of Claim 24, wherein the content of the first audio-visual file is selected by a user for display on the first media player, the user communicating the selection to the controller over [[a]] the data network independent of the coaxial cable network, the display of the content of the first audio-visual file being made in response to

the selection of the first channel using the first media player, the first channel being associated with the first decoder.

26. (Previously Presented) The system of Claim 25, wherein the content of the first audio-visual file is displayed on a second media player in response to a further selection of the first channel using the second media player, wherein the first and second media players are each delivered the content of the first audio-visual file over the first channel for simultaneous display.
27. (New) The system of claim 21, wherein the phone interface is a telephone communicating with the controller through an existing phone system, wherein actions taken by the controller are displayed by a media player in the same room as the telephone, and wherein the user controls playback of the audio-visual file using the telephone.
28. (New) The system of claim 21, wherein the computer interface is a computer in a room with the controller communicating with the controller through a serial connection.
29. (New) The system of claim 28, wherein the computer communicates with the controller through a network connection.
30. (New) The system of claim 21, further comprising:  
a plurality of controllers in communication with the controller
31. (New) The system of claim 21, wherein the separate communications channel is a wireless channel.